



# CYL-V



## Cyl-V Firmware Upgrade Instructions

1. Download the new firmware file "FW\_DV302.BRN" [here](#) and add the file into the root directory of MicroSD Card.
2. Take out the MicroSD card from the PC and insert into Cyl-V Recorder. Then plug it into bracket and power up the unit.
3. Three LEDs will start blinking indicating upgrade is in-progress and all LEDs will automatically turn-off when finished.
4. Connect Cyl-V recorder unit to a PC using USB cable and open up the root directory of Micro SD card and remove the current "config.bin" file.
5. Then, click to open "Cyl-V Settings.exe" file and it will automatically create a new "config.bin" file for you to be able to change settings in the MicroSD card.
6. When finish changing the new settings in the "config.bin" file, click the "Save" button at the bottom and then press "Driver Event Button" on the recorder to update time.
7. Disconnect Cyl-V from PC and power up again in the bracket one more time.
8. Color of PWR LED in the Cyl-V unit will change from red to green indicating Cyl-V unit finished upgrade process and begin recording video with the new firmware.



**A CENTURY OF AUTOMOTIVE VISION SAFETY**

90-21 144th Place, Jamaica, New York 11435  
www.roscomirrors.com www.roscovision.com

For Warranty and Tech Support Contact Rosco at 800-227-2095