

Installation Guideline

Literature Part#: MNLDV408

Proper Antenna Installation

Related Parts:

4G LTE Cellular Antenna for Windshield Mount - DV408

Adhesive Pad for Windshield Mount – DV445

Modem – USA DV405, North America DV425, European DV426

4G LTE Antenna that supports 3G Fall-back

The Manufacture recommends windshield mounting the antenna

NEVER MOUNT THE ANTENNA UNDER METAL PANELS. ANTENNAS NEED A CLEAR VIEW OF THE SKY WITH NO OBSTRUCTION.

Knowing the correct way to position the antenna, and the safe way to mount and coil the excess cable will ensure a strong cellular signal after every install.

- Make sure the windshield mounting location is cleaned before mounting the antenna. A good clean surface will provide a strong hold and prevent the antenna from falling.
- Apply pressure to the antenna for 30 seconds after mounting. This will ensure the entire antenna has contact with the windshield for a strong hold.
- Mount the antenna on the Driver's side, center, or the passenger side lower windshield
- Your antenna should be mounted on the same side as the PDC for easy wire routing
- Connect the antenna to the modem as shown in the photo below (MIMO 1 to PRI & MIMO 2 to DIV)



Installation Guideline

Antenna Mounting:

Make sure you're mounting the antenna the correct way. When mounting to the windshield the flat part of the antenna (top) must have a clear view of the sky.

Top of Antenna (Flat part needs a clear view of the sky). Bottom of Antenna (Curved part) facing inside the vehicle



Extra Antenna Cable:

NEVER TIE OR INTERFERE WITH THE VEHICLES AIRBAG! USE EXTREME CAUTION WHEN ROUTING CABLES IN THE A PILLAR

- Don't bend or fold any excess antenna wire
- Always coil the extra wire without any bends and secure with two zip ties

